

SOFTER N/NS 2.5m – 6m *LINKAGE* Speed Disc



The Softer N 2.5m- 6m linkage range is designed for operators looking for a simple carried machine that is universal in usage from stubble breakdown and incorporation to pre-sowing preparation of the ground after ploughing.

- ♦ Working speed of 10-15kph / Transport max 25kph
- ♦ Working depth of 35 – 120mm
- ♦ 2.5m - 3.5m (N) is rigid with simple manual adjustment of roller (optional weight pack available)
- ♦ 4.5m – 6.0m (NS) is hydraulic folding to 3m wide & **hydraulic adjustment of roller**
- ♦ Maintenance free AGRI-HUB bearings and rubber mounts for long life
- ♦ Frames made with eXtra STEEL line technology for maximum strength
- ♦ Multiple options for different rear rollers to suit your soil types



MODEL	DISCS	DISC SIZE	SPACING	ROLLER TYPE	HITCH TYPE	WORKING WIDTH	TRANSPORT WIDTH	WEIGHT (KG)	REQ HP	RRP EX GST
2.5 N	20	510mm (20")	240mm	600mm TUBE	CAT 2/3 TPH	2.4m	2.5m	1,740	90 – 140	\$27,700
3 N	24	510mm (20")	240mm	600mm TUBE	CAT 2/3 TPH	2.9m	3.0m	1,880	110 – 165	\$31,050
3.5 N	28	510mm (20")	240mm	600mm TUBE	CAT 2/3 TPH	3.4m	3.5m	2,290	120 – 190	\$36,550
4.5 NS	38	560mm (22")	240mm	600mm TUBE	CAT 3	4.5m	3.0m	2,950	160 – 240	\$62,000
5 NS	42	560mm (22")	240mm	600mm TUBE	CAT 3	5.0m	3.0m	3,150	175 – 255	\$69,250
6 NS	50	560mm (22")	240mm	600mm TUBE	CAT 3	6.0m	3.0m	3,650	200 – 300	\$75,250



UPGRADE TO 560mm DISCS	
2.5 N	\$125
3 N	\$152
3.5 N	\$178
4.5 NS	N/A
5 NS	N/A
6 NS	N/A



CHANGE TO VEE ROLLER	
2.5 N	\$1,950
3 N	\$2,050
3.5 N	\$1,980
4.5 NS	\$1,550
5 NS	\$1,950
6 NS	\$4,500



CHANGE TO RING ROLLER	
2.5 N	\$1,500
3 N	\$2,000
3.5 N	\$1,550
4.5 NS	\$4,890
5 NS	\$5,050
6 NS	\$6,700



ADD 340kg WEIGHT PACK	
2.5 N	\$1,095
3 N	\$1,095
3.5 N	\$1,095
4.5 NS	N/A
5 NS	N/A
6 NS	N/A

FOR MORE DETAILS ON OPTIONS PLEASE SEE PAGE 19 OF THIS PRICE BOOK