

1009T GH ²

MOUNTED TANDEM DISK HARROW





The model **1009T GH²** is designed for supplementary soil preparation jobs, such as breaking clods, leveling and the incorporation of lime, fertilizer, herbicides, fungicides and other agricultural chemicals into the soil. It is also very effective for controlling of weeds and weed seedlings.




STANDARD FEATURES:

- Equipped with Category II brackets for universal three point lift arrangement and quick connection.
- 1.1/2" (38.10mm) round heat treated steel gang axles.
- Equipped with TATU oil bath bearing assemblies with tapered roller bearings, duo-cone seals and wear plates.
- Disk blades are heat treated boron steel, notched on front gangs and plain on rear.
- · Adjustable, heavy duty disk scrapers.
- Main frame made of tube with uniform load distribution.
- Several adjustment points allow a great performance in different types of soil.

Lateral displacement on rear gangs.

Cutting Angle:
Several cutting angle
adjustments, without
tooling use, on front and
rear gangs.



RUGGEDLY BUILT FOR LONGER LIFE

TAPERED BEARINGS AND DUO-CONE TYPE SEALS.



SPECIAL **OIL BATH**BEARING ASSEMBLIES

THE LIFE OF YOUR DISK HARROW. REQUIRES ORIGINAL TATU REPLACEMENT PARTS.

TECHNICAL SPECIFICATIONS:

Model	Number of Disc Blades	Working Width ft. in. (mm)		Disc Blades		Weight		Approx.		Tractor
				Dimensions	Spacing	per Disc lbs (Kg)		Net Weight* lbs (Kg)		Draw Bar Horse Power
1009T GH ²	16	6' 3"	(1,908)	18" x 3.0mm		104	(47)	1,677	(761)	70 - 80
	18	7' 7"	(2,315)	or	9"	98	(44)	1,763	(800)	80 - 90
	20	7' 7"	(2,315)	20" x 3.5mm		92	(42)	1,851	(840)	90 - 100
	22	9'	(2,743)			88	(40)	1,940	(880)	100 - 110

^{*} Approx. net weight with 20" x 3.50mm disc blades.

MARCHESAN S.A. reserves the right to perfect or alter the characteristics of its products, without the obligation to do so with those already marketed and without giving prior knowledge. The photos and drawings are merely illustrative. 01/2019 - Rev. 04







MARCHESAN IMPLEMENTOS E MÁQUINAS AGRÍCOLAS TATU S.A.

Av. Marchesan, 1979 - CEP 15994-900 - Matão-SP-Brasil Phone: +55 16 3382.8282 - Fax (Sales): 3382.8297 CNPJ.: 52.311.289/0001-63 - Inscr. Est.: 441.000.151.114

> Approx. depth of cut: 2.3/8" to 4.3/4" (60 - 120mm)