

ROTATING TRENCHER NO-TILLAGE

VA




ROTATING TRENCHER NO-TILLAGE


VA


The VA Rotating Trencher No-Tillage is indicated for drainage processes, water channeling, placement of pipes, drip irrigation or whenever there is a need to open a trench for any purpose.

NOTE: *Indispensable in no-tillage.*

BENEFITS

 Allows the tracing of the ditches in curves, without damaging the machine and the ditch, as it has a directional modeler;


 Make the ditch behind the tractor's right wheel, preventing the formation of three tracks; preventing the formation of three tracks;


 The ditch, for being narrow, allows a better performance of tractors and planters when passing them at planting time;

ROTATING TRENCHER NO-TILLAGE

VA

BENEFITS

 Its control skid keeps the ditch at the desired depth, regardless of terrain irregularities, such as contour lines, track tracks and tires;

 Speed and economy in the construction of trenches.

NOTE: *Option of wide and narrow hoes with 4 working positions.*

ROTATING TRENCHER NO-TILLAGE

VA

IMPLEMENT DETAILS



SPECIFICATIONS

Models VA	40L	55L	75L
Length (mm)	2.150	2.150	2.700
Width (mm)	1.380	1.380	1.350
Height (mm)	1.620	1.620	2.350
Diameter with knives (mm)	990	1.200	1.805
Diameter of rotor without knives (mm)	850	1.060	1.650
Number of blades (um)	20	20	24
Fenders (positions)	Variable	Variable	Variable
Rotor position	Vertical	Vertical	Vertical
Drive	PTO	PTO	PTO
PTO rotation (RPM)	540	540	540
Coupling	3 pts	3 pts	3 pts*
Approximate weight (kg)	435	500	870
Ditch (depth x width) (mm)	A400x90/130 B400x190/230	A550x90/130 B550x190/230	A750x90/130 B750x190/230
Minimum power (hp)**	60	70	120
Operating speed (Km/h)	2.000	2.000	800

NOTE: Two blade widths and 4 positions; * Hydraulic cylinder system;
** Depending on the type of soil.



AGRIMEC AGRO INDUSTRIAL LTDA.

Agricultural Implements.
Address: Pedro Cezar Saccol Ave.
Parque Industrial, Santa Maria - RS

☎ 55 55 3222.7710

📞 55 55 99626.0866